

SVAN 958

Four Channels Sound & Vibration Analyser

The SVAN 958 is all digital, four channels 20 kHz signal analyser including Type 1 sound level meter (meeting IEC 61672) and vibration meter (meeting ISO 8041). It is an ideal choice for the "Human Vibration" (according to the ISO 2631-1,2&5 and ISO 5349-1&2 standards) and noise measurements in the occupational health and safety monitoring tasks. All required weighting filters, along with the necessary accessories for triaxial Whole-Body and triaxial Hand-Arm vibration measurements are available with this instrument.

Each of four channels can work simultaneously with independently configured input (transducer type), filters and RMS detector time constants (e.g. simultaneous three axis measurement of the Whole-Body vibration and noise dose).

Three profiles allow parallel measurements with independently defined filters and RMS detector time constants in each sound channel. Each profile/channel provides "multidimensional" analysis of measured signal (like L_{eq} , L_{Max} , L_{Min} , L_{Peak} , SPL, SEL in the case of sound measurements or RMS, Peak, Peak-Peak, VDV, MTVV in the case of vibration measurements). Advanced time history logging, in non-volatile 32 MB internal memory, provides very powerful measurement capability. USB Memory Stick extends this facility almost unlimitedly. Results can be easily downloaded to any PC using standard USB (or RS 232 or IrDA) interface and SvanPC+ software.

Using computational power of its digital signal processor the SVAN 958 instrument can perform advanced frequency analysis simultaneously to the meter mode:

- real time four channels 1/1 octave or 1/3 octave analysis including statistical calculations

- four channels FFT analysis including cross spectra

- sound intensity measurements.

Reverberation Time measurements, noise dose meter and rotation speed measurements are also available for SVAN 958.

The time domain signal recording on the external USB memory stick is also available as an exceptional feature!

Fast USB 1.1 interface (12 MHz) creates real time link for the PC "front-end" application of the SVAN 958. Instrument can be fully remotely controlled.

Instrument is powered by four AA standard or rechargeable batteries (separate charger is required). The powering of the instrument from the External DC power source or USB interface is also provided.

Robust case and light weight design accomplish the exceptional features of this new generation instrument.

FEATURES

- Four channels, 20 kHz real time, simultaneous sound and vibration measurements
- FFT real time analysis up to 1600 lines in 20.0 kHz band
- 1/1 and 1/3 octave real time analysis
- Human Vibration measurements meeting ISO 8041:2005 including VDV and MTVV
- Noise measurements Type 1, IEC 61672:2002
- Acoustic dose meter function
- Sound Intensity measurements
- Reverberation Time measurements
- Time domain signal recording
- FFT cross spectra
- Advanced Data Logger including spectral analysis
- USB Memory Stick providing almost unlimited logging capability
- Advanced trigger and alarm functions
- USB 1.1 Client and USB Host, RS 232 and IrDA interfaces
- Integration time programmable up to 24 h
- Powered by four AA standard or rechargeable batteries
- Easy in use, hand held, light weight and robust case



TECHNICAL SPECIFICATIONS

VIBRATION LEVEL METER & ANALYSER

| | | |
|-------------------|---|--|
| Standards | ISO 8041:2005 | |
| Meter mode | RMS, VDV, MTVV or MAX, Peak, Peak-Peak | |
| Analyser (option) | Simultaneous measurement in up to four channels with independent set of filters and detector constants | |
| | 1/1 octave* real time analysis, 15 filters with centre frequencies from 1 Hz to 16 kHz (Type 1, IEC 61260) | |
| | 1/3 octave* real time analysis, 45 filters with centre frequencies from 0.8 Hz to 20 kHz (Type 1, IEC 61260) | |
| | FFT* real time analysis up to 1600 lines with Hanning, Kaiser-Bessel or Flat Top window | |
| | FFT* cross spectra measurements | |
| Filters | RPM* rotation speed measurements parallel to the vibration measurement (1 ÷ 99999) and more... | |
| | $W_d, W_k, W_c, W_j, W_m, W_b, W_g$ (ISO 2631), W_h (ISO 5349), HP1, HP3, HP10, Vel1, Vel3, Vel10, VelMF, Dil1, Dil3, Dil10, KB | |
| | RMS & RMQ Detectors | Digital True RMS & RMQ detectors with Peak detection, resolution 0.1 dB |
| | Accelerometer (option) | Time Constants: from 100 ms to 10 s |
| | Measurement Range | SV 39A/L seat accelerometer (100 mV/g sensitivity) for Whole-Body measurements |
| Frequency Range | SV 50 set for Hand-Arm measurements (Dytran 3023M2 accelerometer, 10 mV/g sensitivity) | |
| | Other IEPE accelerometers | |
| | Accelerometer dependent, SV 39A/L seat accelerometer: 0.003 ms ⁻² RMS ÷ 500 ms ⁻² PEAK | |
| | 0.5 Hz ÷ 20 kHz; accelerometer dependent, with Dytran 3023M2: 2 Hz ÷ 10 kHz | |

SOUND LEVEL METER & ANALYSER

| | | |
|-------------------|--|--|
| Standards | Type 1: IEC 61672-1:2002 | |
| Meter mode | SPL, L_{eq} , SEL, L_{den} , L_{tm3} , L_{tm5} , Statistics - L_n (L_1 - L_{99}), L_{Max} , L_{Min} , L_{Peak} | |
| Analyser (option) | Simultaneous measurement in three profiles per channel (up to four channels) with independent set of filters and detector time constants | |
| | 1/1 octave* real time analysis, 15 filters with centre frequencies from 1 Hz to 16 kHz (Type 1, IEC 61260) | |
| | 1/3 octave* real time analysis, 45 filters with centre frequencies from 0.8 Hz to 20 kHz (Type 1, IEC 61260) | |
| | Reverberation Time analysis in 1/3 octave bands (RT 60) | |
| | FFT* real time analysis up to 1600 lines with Hanning, Kaiser-Bessel or Flat Top window | |
| Weighting Filters | FFT* cross spectra measurements | |
| | Sound Intensity Measurements and more... | |
| | RMS Detector | Standard: A, C, Z and G |
| | Microphone (option) | Digital True RMS detector with Peak detection, resolution 0.1 dB |
| | Measurement Range | Time Constants: Slow, Fast, Impulse |
| Frequency Range | SV 22, Type 1, 50 mV/Pa, prepolarised 1/2" condenser microphone with SV 12L preamplifier | |
| | SV 25, Type 2, dose meter, ceramic 1/2" microphone with integrated preamplifier | |
| | Total Dynamic Range: 17 dBA RMS ÷ 140 dBA Peak | |
| | Linearity Range: 24 dBA RMS ÷ 140 dBA Peak | |
| | 0.5 Hz ÷ 20 kHz; microphone dependent, with SV 22 microphone: 10 Hz ÷ 20 kHz | |

BASIC DATA

| | | |
|--------------------------|---|--|
| Input | IEPE type (channels 1, 2, 3 - LEMO 4 pin & channel 4 - TNC connector) | |
| Dynamic Range | 100 dB, 4 x 20 bits A/D converters | |
| Frequency Range | 0.5 Hz ÷ 20 kHz, sampling rate 48 kHz | |
| Data Logger* | Time History logging to internal memory or USB Memory Stick | |
| Display | Time domain signal recording on USB Memory Stick (option) | |
| Memory | LCD 128 x 64 pixels plus icons with backlighting | |
| Interfaces | 32 MB non-volatile flash type, external USB Memory Stick (not included) | |
| Power Supply | USB 1.1 Client, USB 1.1 Host, RS 232 (option: SV 55 required), IrDA (option) | |
| | Extended I/O - AC output (1 V Peak) or Digital Input/Output (Trigger / Pulse) | |
| | Four AA batteries (alkaline) | operation time > 10 h (6.0 V / 1.6 Ah)** |
| | Four AA rechargeable batteries (not included) | operation time > 14 h (4.8 V / 2.6 Ah)** |
| | SA 17A external battery pack (option) | operation time > 24 h*** |
| Environmental Conditions | External power supply | 6 V DC ÷ 15 V DC (1.5 W) |
| | USB interface | 500 mA HUB |
| | Temperature | from -10 °C to 50 °C |
| | Humidity | up to 90 % RH, non-condensed |
| | Dimensions | 140 x 82 x 42 mm |
| Weight | 510 grams with batteries | |

*each function parallel to the meter mode **with USB 1.1 Host function not active and backlight off

Continuous product development and innovation are the policy of our company. Therefore, we reserve the right to change the specifications without prior notice.



SVANTEK

SVANTEK Sp. z o. o.
Pl. Inwalidów 3/62
PL 01-514 WARSAW, POLAND
phone/fax (+48) 22 839 00 31, (+48) 22 839 64 26
<http://www.svantek.com> e-mail: office@svantek.com.pl

ISO 9001
CERTIFIED



UNION FOR ENTERPRISING PEOPLE
COMPETITIVENESS PROGRAMME



EUROPEAN UNION
Project co-financed
by the European Regional Development Fund

DISTRIBUTOR:

SIGMA TEST Messtechnik
Industriepark 312
D-78244 Gottmadingen
Phone +49.7731.977001
Fax +49.7731.977003
info@sigmatest.net
www.sigmatest.net